



> PRINT

**ECOSYS P6030cdn**

COLOUR PRINTER  
FOR A4 FORMAT

# THE FAST NETWORK PERFORMER FOR COLOUR IN A4.



Highly productive and very economical, the compact ECOSYS P6030cdn combines speed and excellent colour quality with intelligent network and security features. This highly efficient combination of features fulfils the demands of busy offices and work groups of nearly all sizes. And thanks to the cost-effective ECOSYS technology with its long-life components, this device offers a great potential for cost savings.

- > Up to 30 pages per minute in A4 in colour and b/w
- > Time to first page 10 seconds (b/w: 8.5 seconds)
- > Up to 9,600 dpi printing quality with multibit technology
- > Standard duplex unit for double-sided printing
- > 500-sheet universal cassette, also for A6 format
- > Up to 5 paper feeders for a paper volume of up to 2,150 sheets
- > Mobile printing support including AirPrint
- > Exceptionally low printing costs in its class



ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

#### PRESCRIBE II c

With the KYOCERA page design and control language PRESCRIBE IIc, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, an integration of graphics into print files is no longer necessary. The printer accesses them as required and thereby reduces network traffic.

#### KYOCERA NetViewer

KYOCERA NetViewer enables the complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunctionals from any Windows® PC and thus gives you the means to streamline your network administration. It also supports standardised SNMP.

#### ECOSYS P6030cdn

##### GENERAL

Technology: KYOCERA ECOSYS, Colour Laser

Control Panel Display: 2 Line LCD back light display

Engine speed: Up to 30 pages per minute in A4 in colour and b/w

Resolution: 600 x 600 dpi

Multibit technology for print quality of up to 9,600 x 600 dpi

Duty cycle: Max. 100,000 pages per month

Warm-up time: Approx. 36 seconds or less from power on

**Time to first page:** Approx. 8.5 seconds or less in b/w  
Approx. 10 seconds or less in colour

Integrated accounting: 100 department codes

Dimensions (W x D x H): Main unit:  
345 mm x 518 mm x 480 mm

Weight: Main unit: approx. 29.5 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption:

Printing: 529 W

Ready mode: 76 W

Low-Power mode: 24 W

Sleep-mode: 4 W

**Noise (Sound pressure level: ISO 7779/ISO 9296):**

Printing in colour: 52,5 dB(A) LpA

Ready mode: 34,4 dB(A) LpA

Sleep mode: Immeasurably low

Safety standards: GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

#### PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 150-sheet multi-purpose tray; 60 – 220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 138 mm – 216 x 356 mm) 500-sheet universal cassette; 60 – 120 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (105 x 148 – 216 x 356 mm). Max. paper capacity incl. options: 2,150 sheets

Duplex functionality as standard: Double-sided printing:

60 – 120 g/m²; A4, A5, B5, Letter, Legal

Output capacity: 250 sheets face-down with paper full sensor

#### CONTROLLER

CPU: Power PC 465S/667MHz

Memory: Standard: 512 MB RAM, max. 1,536 MB RAM

Standard interface: USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT)

Slot for optional internal print server or SSD hard disc

Slot for optional SD/SDHC-Card

Controller language: PRESCRIBE IIc

Emulations: PCL 6 (Sc, XL), KPDL 3 (PostScript 3 compatible), XPS Direct Print, PDF Direct Print 1.7, with automatic emulation sensing

Operating systems: All current Windows operating systems, Mac OS X Version 10.4 or higher, UNIX, LINUX as well as other operating systems on request

Fonts/barcodes: 93 scalable fonts for PCL/PostScript, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

Print features: AirPrint, IPP printing, Email printing, Secure printing via SSL, IPSec, HTTPS, SNMPv3, IPPS, POP over SSL, SMTP over SSL, Private Print, Toner save mode

#### CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19798

**Toner-Kit TK-560C, TK-560M, TK-560Y:** cyan, magenta, yellow toner yield 10,000 pages A4

Starter toner: cyan, magenta, yellow toner yield 5,000 pages A4

**Toner-Kit TK-560K:** black toner yield 12,000 pages A4

Starter toner: black toner yield 6,000 pages A4

#### COMMAND CENTER RX

The Command Centre RX enables to control and manage various settings by accessing the device via a common web browser. It automatically updates screens, customises user screens, and displays department and restriction settings.

#### USB INTERFACE FOR USB FLASH MEMORY DEVICE

Documents can be printed directly from a USB flash memory device via the USB host interface. You can select documents stored as PDF, XPS, TIFF or JPEG directly on the printer's control panel. No computer is required.

#### APPLICATION-BASED PROFILES

The KX printer driver can create a direct link between dedicated applications and predefined or customised print profiles. You can set that all documents from a user or an application be printed in b/w with activated duplex mode as standard, thus leading to a reduced toner and paper consumption.

#### OPTIONS

**PF-500 Paper feeder:** 500 sheets; 60 – 120 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm)

**PF-510 Paper feeder:** 500 sheets; 60 – 220 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 216 x 356 mm)

**CB-500 Cabinet:** Wooden desk with storage capacity.  
Approx. 38.5 cm x 50 cm x 58 cm (W x H x D)

Memory upgrade: MDDR3-1GB: 1.024 MB

**HD-6 SSD hard disc:** 32 GB for easy document management

**HD-7 SSD hard disc:** 128 GB for easy document management

Optional interfaces:

**IB-50 Gigabit Ethernet:** 10BaseT/100BaseTX/1000BaseT (RJ-45)

**IB-51 Wireless LAN:** 802.11b/g/n

#### MODEL VARIATIONS

**ECOSYS P6030cdn/KL3:** ECOSYS P6030cdn incl. warranty extension KYOLife 3 years

#### WARRANTY

1-year warranty as standard.\* KYOCERA guarantees the drums and developers for 3 years or maximum 200,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.



The up to 5-year on-site warranty extension for printer and options.



**LASERLIFE**  
MANAGED PRINT SOLUTIONS

15 Tennis Street  
London, SE1 1YD  
0207 403 6866  
info@laserlife.co.uk  
www.laserlife.co.uk

KYOCERA Document Solutions Europe B.V. – Branch Office Germany  
Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany  
Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100  
www.kyoceradocumentsolutions.eu – info@deu.kyocera.com

KYOCERA Document Solutions Inc. – 2-28, 1-Chome – Tamatsukuri – Chuo-Ku  
Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

\*Depending on the country.

YOUR KYOCERA BUSINESS PARTNER

**KYOCERA**  
Document Solutions